

Description

PE coated photographic paper (150 g/m²) white, with one sided gloss inkjet coating.

Release paper

Silicone coated paper, 98 g/m²

Adhesive

Polyacrylate, permanent, transparent

Area of use

For colourful, photorealistic large format prints. Not suitable for outdoor applications.

Printing method

Waterbased inkjet printing, dye and pigmented inks

Recommended printers

Look at www.orafol.de for recommended inkjet printers

Technical data

Thickness* (without protective paper and adhesive) 150 micron

Temperature resistance adhered to aluminium, -20°C to +60°C, no variation

Adhesive power* 16 N/25 mm
(FINAT TM 1, after 24h, stainless steel)

Shelf life** 1 year

Application temperature min. +10°C

* average ** in original packaging, at 20°C and 50% relative humidity

Attention:

After printing the ink must be thoroughly dry in order to avoid any affect on the later combination with the laminate. Surfaces to which the material will be applied must be thoroughly cleaned from dust, grease or any contamination which could affect the adhesion of the material. Freshly lacquered or painted surfaces should be allowed to dry for at least three weeks and to completely cure respectively. The compatibility of selected lacquers and paints should be tested by the user, prior to application of the material. Furthermore the application informations published by ORAFOL are to be considered.

The statements in this information sheet are based upon our knowledge and practical experience. This data is intended only as a source of information and is given without guarantee and does not constitute a warranty. Due to the wide variety of possible uses and applications customers should independently determine the suitability of this material for their specific purpose, prior to use.

