

# ORATAPE

## MT 80P Application Tape

07/16

### Description

Transparent PVC-based mounting film, covered, for the transfer of die-cut and computer-cut letters and symbols.

### Release paper

One-sided siliconized glassine paper, white, 62 g/m<sup>2</sup>.

### Adhesive

Modified Solvent polyacrylate, medium adhesive strength.

### Area of use

The special composition of the polyacrylate adhesive enables unproblematic transfer of die-cut and computer-cut letters and symbols. Even after more than six months of application, a residueless removal without any considerable increase in adhesive strength has been proven. The high tensile strength of the film ensures precise positioning. Recommended for all applications, where repeated use of the film tape is requested. The check print of the release paper facilitates the exact cutting of the sections.

### Technical data

---

**Thickness** (film with adhesive, without protecti 100 micron

---

**Adhesive power\***

(FINAT TM 1, after 20min, stainless steel) 2 N/25mm

---

**Tensile strength** (DIN EN ISO 527)

along min. 19 MPa

---

**Elongation at break** (DIN EN ISO 527)

along min. 130%

---

**Shelf life\*\***

2 years

---

**Application temperature**

min. +10°C

---

\* average      \*\* in original packaging, at 20°C and 50% relative humidity

The statements in this information sheet are based upon our knowledge and practical experience. This data is intended only as a source of information and is given without guarantee and does not constitute a warranty. Due to the wide variety of possible uses and applications customers should independently determine the suitability of this material for their specific purpose, prior to use.



ORAFOL Europe GmbH - Am Biotop 2 - D 16515 Oranienburg  
Telefon: +49 (0) 33 01/864 0 - Telefax: +49 (0) 33 01/864 100  
E-Mail: [verkauf@orafol.de](mailto:verkauf@orafol.de) - Internet: <http://www.orafol.d>