

Description

This double-sided tape consists of a polyester film carrier, layered on both sides with a solvent acrylate adhesive.

Carrier

Polyester film, 12 micron

Liner

white paper, both sides coated with silicone, 80 g/m²

Adhesive

Solvent acrylate

Area of use

Used for the lamination of paper, films and textile surfaces.

Technical Data

Thickness* (adhesive + carrier)	70 micron
Temperature resistance***	-40° C to +140° C
Adhesive power* (FINAT TM 1, on stainless steel, one side covered with 50 micron polyester film)	after 1 min 10 N/25 mm after 20 min 11 N/25 mm after 24 h 12 N/25 mm
Shear strength* (FINAT TM 8, on stainless steel, one side covered with 50 micron polyester film)	> 1000 h at 23° C > 72 h at 70° C
Shelf life**	2 years
Application temperature	> +15° C

* average ** in original packaging, at 20° C and 50% relative humidity *** 1h, normal climate of Central Europe

IMPORTANT NOTICE

All ORABOND® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORABOND® products is based upon research which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORABOND® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

ORABOND® is a registered trademark of ORAFOL Europe GmbH.