



Product Sheet

Mod.R&S.05 | Rev.4 | Update 11/2017



SWING & PULL

Description SWING & PULL is Siser's new heat press - it opens laterally and lower plate slides frontally, in order to speed and facilitate the positioning of the garment.

A very homogeneous pressure is ensured by the mechanical closure system, and it is provided with an electronical display showing pressure and reminding you when transfers are ready.

Optional Plates
Plates for caps
Plates for shoes (Options H+Achlle)
Logo platens 15x15 cm
30x15 cm
38x10 cm

Technical Data

| | |
|-------------------|------------------------|
| Power | 2000 Watt |
| Voltage | 220 Volt |
| Max Temperature | 220° C |
| Max Pressure | 300 gr/cm ² |
| Plates dimensions | 38cm x 50cm |
| Weight | 58 kg |



The SWING & PULL machine, as it is equipped with electrical parts operating at a voltage between 50 V and 1000 V, is subject to the Low Voltage Directive 2014/35/UE (formerly 2006/95/CE) and the Electromagnetic Compatibility Directive 2004/108/EEC.

Since there are no motor-driven moving parts, as the movement of closure and opening of the plates is controlled by hand, the SWING & PULL does not come within the field of application of the Machinery Directive 2006/42/CE. Nevertheless, the design and construction of the SWING & PULL has been made in compliance with the essential safety requisites foreseen by Directive.



Siser s.r.l.
Viale della Tecnica n°18
36100 Vicenza - Italy

Tel. +39 0444.287960
Fax +39 0444.287959
info@siser.it - www.siser.com

r.e.a. vi 171856
reg. imp. vi n° 14971
c.s. € 103.300 i.v.
p.iva 01591490246