

DATA SHEET 22157.310.35800

# SI 157

Ink Jet Canvas for framed printings or for stretching on wooden frames. Material 30 / 70% polyester / cotton, coated on one side, with natural structured surface. Suitable for art prints, lifestyle posters, exhibition work and stage decoration.

## **Printing Systems**



Rolls				
Art.Number	Width (mm)	Grammage	Length (m)	
22157.310.35800	610	310 g/m²	15	
22157.310.38900	914	310 g/m²	15	
22157.310.30400	1067	310 g/m²	15	
22157.310.30900	1118	310 g/m²	15	
22157.310.34900	1520	310 g/m²	15	

## **Technical data**

#### Characteristic

- High brillance of colours
- Flexible coating for good strechability
- Natural finish on the reverse side
- Low-reflective printing surface
- Tear resistant

Finish

• Natural, semi matt

#### **Specifications**



Coating Printside	microporous coating	
Width (mm)	610	
Grammage	310 g/m²	
Core Diameter	76 mm	
Length (m)	15	
Base Material	Polycotton (70% cotton, 30% polyester),	
	1:1 weave	
Packing quantity	1 roll	

#### Compatibility

• Suitable for most large format Ink Jet printers using waterbased dye, pigment or latex inks

### Handling

- An additional protection of the printed surface is required when it is subject to abrasion, hand perspiration or other mechanical influences. In this case the print must be protected with a suitable clear varnish or a liquid lamination product.
- When using dye inks, the printed image must be protected in any case with a clear varnish or a liquid lamination product in order to improve the colour fastness.

#### Storage

• Store in a cool and ry place at a room temperature of 15 - 25°C and at a humidity of 30 - 60%.

#### Product liability clause

The foregoing information and any consulting provided by us in terms of application engineering shall be given to our best knowledge, but shall not be considered binding information neither with regard to any third party industrial property rights. Any such consulting shall not relieve you from your own review of our current consulting information as to their suitability for the intended procedures and applications. These shall be beyond our control, and be subject to your exclusive responsibility. The sale of our products shall be subject to our current General Terms and Conditions.