

DATA SHEET 29721.175.84500

BG-72.1

A crystal clear film, for Colour Laser Printers using high fusing temperature toners. Ideally suited for overhead projection transparencies or see through overlays. The film uses the same universal coating on both sides, eliminating any confusion when inserting sheets into the feed tray.

Printing Systems



Formats

Art.Number	Format	Nominal thickness (mm)	Packing quantity
29721.125.84500	SRA3	0.125	200
29721.175.84500	SRA3	0.175	200

Technical data

Characteristic



- True colour
- For machines equipped with optical sensors
- Also suitable for machines with high fixing temperature
- Excellent runnability
- Good flatness
- Excellent toner bonding
- Heat resistant
- Highly universal

Finish

- Clear transparent
- Paper backed short side

Specifications

Coating Printsides	Laser & Copier colour
Width (inch)	12.6
Width (mm)	320
Printside	Special coating for toner
Format	SRA3
Length (inch)	17.72
Length (mm)	450
Nominal thickness (mil)	7
Nominal thickness (mm)	0.175
Backside	Paperbacked short side
Base Material	Polyester film
Packing quantity	200

Compatibility

- For use on most Mono & Colour Laser Printers.

Handling

- Please follow the handling instructions supplied with this product as well as the Copier / Printer manufacturers manual.
- Avoid moisture and fingerprints.

Storage

- Store in a cool and dry place at a room temperature of 15 - 25°C and at a humidity of 30 - 60%.

Product liability clause

The foregoing information and any consulting provided by us in terms of application engineering shall be given to our best knowledge, but shall not be considered binding information neither with regard to any third party industrial property rights. Any such consulting shall not relieve you from your own review of our current consulting information as to their suitability for the intended procedures and applications. It is the users responsibility to determine the suitability for his/her own use and application and test through the complete production process to ensure the product is fully suitable for the intended use, since conditions of use are beyond our control. The sale of our products shall be subject to our current General Terms and Conditions. We reserve the right to make changes that serve to improve the product.