

### FUSION BANNER Déco TEX 440

CT-SP440

Item	Description	Specification	
Fabric Structure	Fabric Tenacity (DIN EN ISO 2060)	High Tenacity Yarns 100% PES (500D*500D)	
	Construction (Weaving)	9*9/inch <sup>2</sup>	
	Weight of Fabric	120 gr/m <sup>2</sup>	
	Breaking Tensile Strength DIN 53354	Warp: 850/Weft: 750	N/5 cm
	Tearing Strength DIN 53356	Warp: 150/Weft: 120	N/5 cm
Lamination Structure	Type of Structure	Fabric Roll Bi-laminated with 115my of Soft Vinyl	
	Calibrated Bilamination Adhesion DIN 53357	60 N/5 cm	
	Total Weight of the Composite	440 ± 10 gr/m <sup>2</sup>	
	Surface Finish	Decorative embossing	
	Colour	White (One Side Printing)	
	Available Sizes	1,12 – 1,60*30m	
Applications	Fusion technology, ideal for decoration and interior design. Good digital printability, high intensity and durability.		
Storage Period	2 years at the temperature limit of -5 °C / +45 °C. To be kept in dry places and within the original packaging.		
Technical Limitation	The product can resist at the operating temperature of -20 °C / +60 °C. The product can resist at the limit temperature of -30 °C / +60 °C for a short time.		
Printing Compatibility	<ul style="list-style-type: none"> <li>- Suitable for Digital and Silk Screen printing.</li> <li>- Suitable for solvent, eco-solvent, UV inks and Latex (Latex: tested on Mimaki JV400LX and HP 300/3000 series; when working with other machines, tests before printing are recommended).</li> <li>- All tests are made with the original printer manufacturer's inks on the following equipments: Roland, Mimaki, Dust and HP.</li> <li>- Notes: due to the wide number of ink producers and Digital Printing machines, weather conditions and printing variability, testing before printing is recommended.</li> </ul>		
Options	The product is classified in class 2 (DIN 4102-B2) as flame retardant. It can be produced in class 1 (B1) without any variation to its mechanical and thermal characteristics.		
Safety Caution	<p><b>REACH</b> - Complying with the Italian Decree-Law nbr. 133 issued on 14.09.2009 published on the Italian Gazzetta Ufficiale, we inform that the substance Bis(2-ethyl(hexyl)phthalate (DEHP) is present in a concentration of 14,77%. For further information, please refer to the certified copy available of the analyses worked out on the substances taken into consideration by REACH (Registration Evaluation Authorization of CHemicals).</p> <p><b>RoHS</b> - The product is in accordance with RoHS directive 2002/95/EC and its amendment directives.</p>		
Notes	<p><i>Published information is based upon research and information which the Company believes to be reliable although such information does not constitute a warranty.</i></p> <p><i>Because of the variety of uses of the products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. The seller shall not be liable for damages in excess of the purchase price of the product nor for incidental or consequential damages. All specifications are subject to changes without prior notice.</i></p>		