



Product Information

Mod.R&S 06 | Rev.4 | Update 08/2019 | Page 1



EASY SUBLI

Description Thermotransfer film with plain polyester backing, designed for sublimation ink printers.

It grants vibrant colours and a stunning thin design on the garment and allows to decorate cotton fabrics with sublimation inks.

Suitable textiles: cotton (all colors) and white/light colored polyester or poly/cotton blend, not treated.

Usage **Given the large number of sublimation inks and printers, we highly recommend performing a print and cut test before entering into production.**

- Print and cut the material
- Weed the exceeding material
- Remove the print from its polyester support by hand, then place it on the t-shirt
- Cover the print with silicon paper, baking paper or parchment paper
- *In case of pre-cut letters or numbers use our TTD Special application tape to remove the print from the carrier, then place it on the t-shirt.*
- Heat apply at the conditions shown on the right
- Remove the cover paper warm
- *If you used our TTD Special application tape, remove it warm.*

Washing Wait at least **24 hours** from application before washing.

Washing resistance up to **60°C**, best inside-out.

Do not use bleach or other aggressive chemical agents.

Not suitable for dry cleaning.

Suitable for tumble dryer, synthetic cycle.

The product is REACH compliant

The product is certified Öko-Tex® Standard 100 Class I

This product id VEGANOK certified



N.B. All information here contained are based on our experience.
 We always recommend to perform a test before starting standard production.
 For best results we suggest to store the product standing, away from sunlight at temperatures between 18°C and 26°C



Management System
ISO 9001:2015
ISO 14001:2015

www.tuv.com
ID 9105027958



The product meets the Italian and EU regulations relating to its proper use, and to the (EU) regulation n. 1907/2006/EU REACH (Registration, Evaluation, Authorization and Restriction of Chemical substance).

This document can be subject to variations. Updated versions are available on our website www.siser.com

For further information, please contact our Sales Office.

Average thickness
220 microns

Suggested cutting settings
Blade: **45°**
Pressure: **120 gf**
Speed: **20 cm/sec**

Transfer settings
15 seconds at 155°C (311°F)
medium pressure (3-4 bar)

Washing temperature



Dry cleaning



Tumble dryer



Siser s.r.l.
Viale della Tecnica, 18
36100 Vicenza - Italy

Tel. +39 0444.287960
Fax +39 0444.287959
info@siser.it - www.siser.com

r.e.a. vi 171856
reg. imp. vi n° 14971
c.s. € 103.300 i.v.
p.iva 01591490246

