

TEXTILE

Technical Bulletin

TAP-SELF-ADHESIVE POLYESTER

ELEMENT	DESCRIPTION	NORM	UNIT	VALUE
PRODUCT	Article code			TAP-2730-07 - TAP-2730-13
	Available size		m	1,07-1,27*30m
	Composition	DIN 60001; ASTM D7641	%	100% polyester
	Total weight		gr/m ²	370 ± 20
	Total thickness		micron	350 ± 20
	Finish (60°)	GB/T 9754-2007	gloss unit	3-5
BASE FABRIC	Weaving			plain weave
	Pattern			taffetà
	Colour			white
	Thickness		gr/m ²	270 ± 20
	Whiteness	ISO11475		120 ± 10
	Warp Yarn Count + Type	UNI EN ISO 2060	DEN	300
	Weft Yarn Count + Type	UNI EN ISO 2060	DEN	300
ADHESIVE-TECHNICAL DATA	Type			water base removable adhesive
	Peeling force (15 min)	FTM1/FINAT	bf/in	0.5 ÷ 1.5
	Peeling force (24 hrs)	FTM1/FINAT	bf/in	1.5 ÷ 2.0
	Type			Kraft coated paper
	Weight		gr/m ²	100 ± 5
	Thickness		micron	110 ± 5

APPLICATIONS	Adhesive polyester textile. Its closed and flat yarn structure enables a good printing resolution and a colour full brightness. A more opaque and thick surface and a textile touch make it perfect for wall covering applications. Suitable for labelling, wall display, marathons and pedestrian races.
PRINTABILITY	For ink-jet : latex, eco-solvent and UV inks. For screen printing : with all inks from the series. Notes : due to the wide variety of UV inks products and digital printing machines, testing before printing is always recommended.
STORAGE	12 months under normal conditions at an average temperature of 22 °C (min. 12 °C, max. 32 °C) and a relative humidity of 45 - 65%. The material should be stored in its boxes and not exposed to sunlight.
SAFETY REGULATIONS	REACH - Complying with the Italian Decree-Law nbr. 133 issued on 14.09.2009 published on the Italian Gazzetta Ufficiale, we inform that no SVHC are present in a concentration exceeding 0,1% in the base fabric nor in the coating. For further information, please ask for the updated regulation of SVHC taken into consideration by REACH (Registration Evaluation Authorization of CHemicals).
NOTES	<i>Published information is based upon research and information which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of the products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. The seller shall not be liable for damages in excess of the purchase price of the product nor for incidental or consequential damages. All specifications are subject to changes without prior notice.</i>