

Protection for vehicles. Profits for you.

Add Protekt® PPF by Madico® to your portfolio and you'll be driving traffic and profits to your business.



PROTEKT® PPF
BY MADICO

The Best Place to Start for the Perfect Finish.

Protekt® PPF's protective qualities and durability make it the superior choice among paint protection films.



Protekt PPF can easily be cut with Madico's MACS plotter system to provide a tailored fit on any vehicle surface. Its proprietary, industry-leading, self-healing top coat resists scratches, chemicals, and pollution. Protekt is manufactured with a cap sheet to protect it during shipping, handling and storage.

Technical Information and Measurements

Tensile Strength	41.0 MPa (5,950 PSI)	ASTM D-412
Elongation at Break	458%	ASTM D-412
Adhesive	Acrylic	High Tack Removable
Adhesive Peel Force	946 - 1303 gm/cm (5.3-7.3 lbs./in.)	PSTC 101
Film Thickness	185 Microns (7.3 mil)	Applied Product
Structural component	150 Microns (6 mil)	Polyurethane
Liner	76 Microns (3 Mil)	Siliconized Polyester

Specification Use Statement

Reported values are typical properties and should not be used as a specification. Since the user is aware of the specific conditions in which the product is to be used, it is the user's responsibility to determine whether the product is suitable for intended use. If you need verification regarding specific use or additional information, please contact Madico or your local Madico Authorized Dealer.

