



FOLAPROOF PTDP-SM

FOLAPROOF Ink-Jet Paper for Piezo and Thermal Printers, satin

FOLAPROOF PTDP-SM coating is a highly absorbent microporous layer, which allows inks to quickly penetrate the surface and appear dry almost instantly. Dye based inks will be immediately touch dry, pigmented inks may take a few minutes more depending on the ink density. The coating also has very good splash resistance properties.



Characteristic

- Suitable for Thermal Ink Jet printer
- Suitable for Piezo Ink Jet printer
- Suitable for pigment inks which offers improved light stability
- Suitable for Latex printers
- Suitable for Dye Ink
- Instant dry coating
- Single, microporous coated photopaper
- True colour
- Good flatness
- Good image resistance to physical attacks as UV fading and colour shift but only for a certain period of time.
- Splash resistant surface

Finish

- Satin Surface

Specifications

• Coating frontside	For Ink Jet
• Print side	Semi-Matt Side
• Base material	Paper
• Width (mm)	1067
• Length (m)	20
• Width (inch)	42
• Length (ft)	65.62
• Basic weight (oz)	7.41
• Basic weight (g)	210
• Packing quantity	1

Compatibility

- Suitable for most large format Ink Jet printers using waterbased dye or pigment inks
- Not compatible with oil and solvent based systems.

Handling

- Between 15-30°C and 30-70% r.h.
- A preconditioning period of 24 hours within the printing environment is recommended.
- Avoid fingerprints on printing side.
- Print side = matt white side
- Lamination: cold or heat lamination. To increase UV Protection, laminating is recommended.

Storage

- Store in a cool and dry place at a room temperature of 15 - 25°C and at a humidity of 30 - 60%.

Further Articles

Rolls

Art. Number	Basic weight (g)	Width (mm)	Length (m)
23728.210.34000	210	431	20
23728.210.35900	210	610	20
23728.210.39000	210	914	20
23728.210.30500	210	1067	20
23728.210.31000	210	1118	20

23728.210.32000	210	1270	20
23728.210.35000	210	1524	20