



# DATA SHEET 30305.100.44000

# Long Life

A white film for extreme internal or external applications. It is tear resistant and an ideal substitute for manuals, maps, clean room conditions, signs, etc, where paper is not resilient enough.

# **Printing Systems**









### **Formats**

Art.Number	Nominal thickness	Format	Packing quantity
	(mm)		
30305.100.44000	0.100	A4	100

### Technical data

### Characteristic

- True colour
- Fibre free
- Suitable for Colour Copier
- Suitable for Colour Laser Printer
- Suitable for Mono Copier
- Suitable for Mono Laser Printer
- Excellent toner bonding
- Heat resistant
- Tear resistant
- Improved water resistance

# **Finish**

• White glossy



### **Specifications**

Nominal thickness (mil)	4
Nominal thickness (mm)	0.100
Coating Printside	Special reactive coating for toner
Width (inch)	8.27
Width (mm)	210
Printside	Printable both sides
Format	A4
Length (inch)	11.69
Length (mm)	297
Base Material	Polyester film
Packing quantity	100

# Compatibility

• Suitable for primarily black and white laser printers and copiers. Due also be used on color laser printers and - copiers.

## Handling

- Please follow the handling instructions supplied with this product as well as the Copier / Printer manufacturers manual.
- Avoid moisture and fingerprints.

## Storage

- Once packaging is opened, store at a room temperature of 15 25°C and at a humidity of 30 60 %
- Store in a cool and dry place

### Product liability clause

The foregoing information and any consulting provided by us in terms of application engineering shall be given to our best knowledge, but shall not be considered binding information neither with regard to any third party industrial property rights. Any such consulting shall not relieve you from your own review of our current consulting information as to their suitability for the intended procedures and applications. These shall be beyond our control, and be subject to your exclusive responsibility. The sale of our products shall be subject to our current General Terms and Conditions.





