

DATA SHEET 2999W.050.84500

CLP Adhesive P WO

Gloss white permanent self-adhesive film with a silicon paper release liner. Ideal for stickers, signs, decals and posters. Tear resistant and can be used in worst internal or external conditions. The imaged film has outstanding toner bonding, is water resistant and can be used in all weather conditions.

Printing Systems



Formats

Art.Number	Format	Nominal thickness (mm)	Packing quantity
2999W.050.84500	SRA3	0.050	200

Technical data

Characteristic



- True colour
- Suitable for Colour Copier
- Suitable for Colour Laser Printer
- Excellent toner bonding
- Tear resistant
- Splash resistant

Finish

- White glossy

Specifications

Coating Printsideside	Laser & Copier colour
Width (inch)	12.6
Width (mm)	320
Printside	Special reactive coating for toner
Format	SRA3
Adhesion strength	~ 3.5 - 5.0 N / 25 mm (A.F.E.R.A.), after 24 h ~ 10 N / 25 mm (A.F.E.R.A.)
Type of adhesive	dispersion
Length (inch)	17.72
Length (mm)	450
Nominal thickness (mil)	2
Nominal thickness (mm)	0.050
Backside	Self adhesive with paper release liner
Temperature range	glued +5°C up to +80°C
Base Material	Polyester film
Packing quantity	200

Compatibility

- For use on most Mono & Colour Laser Printers.

Handling

- Please follow the handling instructions supplied with this product as well as the Copier / Printer manufacturers manual.
- Surface Protection: The product can be used outdoor without lamination. However, the surface must be protected in order to improve weathering resistance or if the film is subject to any mechanical influences. In this case you should use self-adhesive laminating foils. If silicon oil is added depending on the type of machine this may influence the adherence of the laminating foil on the film's surface. It is necessary to make some tests on a sample sheet before further processing.
- Adhesive: The product will stick to any solid, smooth surfaces which are dry and free of dirt, oil, silicon etc. The temperature during the application must reach at least 15°C.
- Avoid moisture and fingerprints.

Storage

- Store in a cool and dry place at a room temperature of 15 - 25°C and at a humidity of 30 - 60%.

Product liability clause

The foregoing information and any consulting provided by us in terms of application engineering shall be given to our best knowledge, but shall not be considered binding information neither with regard to any third party industrial property rights. Any such consulting shall not relieve you from your own review of our current consulting information as to their suitability for the intended procedures and applications. These shall be beyond our control, and be subject to your exclusive responsibility. The sale of our products shall be

subject to our current General Terms and Conditions.

DIGITAL PRINTING



DIGITAL PRINTING MEDIA
DIGITALDRUCK MEDIEN
SUPPORTS POUR IMPRESSION NUMÉRIQUE
SUPPORTI PER LA STAMPA DIGITALE
SOPORTE PARA IMPRESION DIGITAL

folex[®]
I M A G I N G

CLP Adhesive P WO
0.050 mm
100 Sheets SRA3