



**INNOVATIVE**

**SCR 360  
REAR PROJECTION**

**INDOOR INSTALLATION**



**PROJECTION FILM**

**DESCRIPTION**

This revolutionary film will allow you to keep all your data safe from prying eyes (depending on the technology of the screen used). The application is to be carried out on the glazed surfaces of the offices.



**Durability:** 12 to 15 years for a vertical application in Central Europe.



**Use:** for all types of glass.



**Maintenance :** after 30 days with a usual cleaning solution (non abrasive, without ammonia...). Cleaning products that could scratch are not recommended.



**Storage:** 2 years from delivery. This film must be stored away from excessive humidity and sunlight, at a temperature below 38°C.

In order to meet high standards, we recommend that you do not mix films from different productions


**INFORMATION**

**SUPPORT :** .....PET  
**ADHESIVE :** .....Acrylic polymer 25 G/M<sup>2</sup>  
**PROTECTOR :** .....Siliconized PET 23 microns  
**THICKNESS :** .....100 microns  
**COLOR :** .....Colorless  
**APPLICATION SIDE :** .....Internal  
**TRANSMISSION LUMIÈRE :** .....88%  
**VIEWING ANGLE :** .....180°  
**APPLICATION T° :** .....min, + 5°C  
**STANDARDS :** .....EUROCLASSES  
**FIRE RATING :** ..... B-s1,d0  
**GUARANTEE :** .....5 years\*

\* For glazing not exposed to the sun

**DIMENSIONS**

Cutting by the linear meter



Application Note



Video of the installation



**Method of application**

The surface to be bonded must be free of dust, grease or any other contaminant. Some materials such as polycarbonate can cause bubbling problems. A compatibility test is therefore recommended. Possibility to install on plexiglass and polycarbonate.

**Production monitoring and standards**

In order to constantly improve our productions, we may have to modify without notice the colors and manufacturing processes. We recommend to our users, before applying our films, to make sure that they are exactly suitable for the intended use and to comply with the standards in force.