



U.V. Canvas New Lisboa

Data Sheet

Description

Material	100 % cotton canvas coated on one side
Coating	White, satin coating
Properties	High stability against environmental influences Fast drying Satin colour reproduction No reflections on the printed surface Natural coloured textile backing Further processing by sewing or eyeleting possible Suitable for stretching on stretched bars (no cracking on edges)
Application	For indoor signs, framed art, outdoor signage, art prints (clichés), poster, exhibition works, stage decoration...
Durability	For medium-term use depending on the ink type
Inks	Solvent, Ecosolvent, Latex y U.V. curable

Laminating

We recommend protecting the printer surface when it is subjected to abrasion, moisture or other mechanical influences. In this case, we recommend protecting the image with an appropriate liquid lamination.

Technical Data

Material	100% cotton canvas
Thickness	440 µm
Weight	300 g/m ²
Dimensions	<div style="display: flex; justify-content: space-around;"><div style="text-align: center;">1067 mm - 42"</div><div style="text-align: center;">1370 mm - 54"</div><div style="text-align: center;">1600 mm - 63"</div></div> <div style="display: flex; justify-content: space-around; margin-top: 10px;"><div style="text-align: center;">2100 mm - 83"</div><div style="text-align: center;">2600 mm - 103"</div><div style="text-align: center;">3100 mm - 122"</div></div>
Roll length	25 m (any other length can be produced under request)

Storage

After printing we recommend to remove the remaining roll from the plotter and to keep the canvas in the original packaging in a cool and dry environment.

Notes

Due to the natural components of the cotton in the raw textile, the surface finish of the media can slightly vary. Also, slight colour deviations can occur from production to production.