



Wall Deco Textile High Tack

Description

| | |
|--------------------|--|
| Material | 100% polyester fabric, self-adhesive, coated on both sides. |
| Coating | White satin coating on the front side and permanent adhesive on the back side. |
| Properties | High stability against environmental influences Fast drying White satin colour reproduction Glare-free printing Suitable for use as decorative wallpaper Excellent application features, providing excellent adhesion on a wide variety of products such as plastics, wood, glass, aluminium and other metals. Permanent adhesive with good bond strength. |
| Application | Interior, decorative prints and wallpaper. |
| Durability | Medium term, depending on the type of ink used. |
| Inks | Eco solvent, solvent, latex and UV-curable inks |

Laminating

We recommend to protect the printed surface when it is subject to abrasion, or other mechanical influences. In this case, we recommend to use varnish with U.V. protection.

Technical data

| | |
|-------------------------------------|---|
| Fabric base | 100% polyester fabric, 230 g/m ² , 240 μ , white satin coating |
| Adhesive | UV-curable PSA acrylic adhesive, 30 g/m ² |
| Liner | CCK paper, 120 gsm |
| Final product | Self-adhesive 100% polyester textile, white satin coating |
| Weight | 340 g/m ² |
| Peel (FINAT FTM1 method) | After 20 min. 15 to 18 N/25 mm |

Availabilities

1370 mm

54"

Roll length 20m (any other length can be produced under request)

Storage

After printing we recommend to remove the remaining roll from the plotter and to keep the canvas in the original packaging in a cool and dry environment.

Note

Slight colour deviations can occur from production to production.