Magnetic Sheeting – Natural

Technical data:

PRODUCT DESCRIPTION: ROLL NATURAL (RAW, BROWN)
THICKNESS: 0.4 MM

COMPOSITION:

- magnetic powder
- chlorinated polyethylene
- soybean oil

PHYSICAL DATA:

BM Art.	Thickness	Dimension (L x B)		Pole pitch	Pull strength	GW
705.002/031	0.4 mm (+/-0.03)	30.000 mm (+200)	615 mm (+2/-0)	2 mm	>18 G/CM2	30 Kg
705.004/031	0.4 mm (+/-0.03)	20.000 mm (+300)	1030 mm (+3/-0)	2 mm	>18 G/CM2	33 Kg
705.016/031	0.4 mm (+/-0.03)	20.000 mm (+300)	1270 mm (+3/-0)	2 mm	>18 G/CM2	42 Kg

PHYSICAL PROPERTIES:
From a temperature of +30°C, the magnetic foil could lose certain % of its adhesive strength.
Magnetic sheet has a UV hardened coating on the magnetic side.
Scissor cutting, knife-cutting, die-cutting and slitting can be done with ease.

- Working Temperature: - 10°C / + 50°C
- Short Term Resistance: 60°C

The material is classified as non-toxic according to EU directives and TSCA (Toxic Substances Control Act), classified as environmentally neutral, REACH and RoHS compliant.

CUSTOM TARIFF NO. (TARIC-Code): 8505 190090